

SIEMENS

HVAC Products

RWB27



Timed control of Central Heating

RWB29



Programmable control of Hot Water and Central Heating

The new range of RWB controllers - quality, innovation and style.

- Unique menu driven programming
- Easy to read, larger than average backlit display
- Simple operation
- Up to 3 hour boost facility
- 2/3 ON/OFFs
- Holiday programming
- Universal programming
 - Daily
 - Weekday/Weekend
 - 7 Day
- Programmable away from its backplate
- Industry standard backplate
- Battery back-up

Overview of the new RWB27 timeswitch and RWB29 programmer.



RWB 27 Timeswitch

Technical Data

Operating Voltage	220/240V
Switching Voltage	12/240V
Frequency	50Hz
Contact rating	
– (resistive)	6A
– (inductive)	2A
Ambient temp. range	0°C to 40°C
Environmental humidity	80% RH
Housing	ABS resistant to fire as IEC 730 standard
Dimensions	145mm wide x 90mm high x 34mm deep

Ordering Specification

Description	Type
Single channel timeswitch with one volt free changeover contact	RWB27



RWB 29 Programmer

Technical Data

Voltage	220/240V
Frequency	50Hz
Contact rating	
– (resistive)	6A
– (inductive)	2A
Ambient temp. range	0°C to 40°C
Environmental humidity	80% RH
Housing	ABS resistant to fire as IEC 730 standard
Dimensions	145mm wide x 90mm high x 34mm deep

Ordering Specification

Description	Type
Two channel programmer with two changeover contacts	RWB29